

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 1 of 14

Rigid 10K Resin

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name: Rigid 10K Resin

Product code: FLRG1001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: For use in Formlabs SLA Printers

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

1.3 Details of the manufacturer/supplier of the safety data sheet

Manufacturer:

United States

Formlabs, Inc
35 Medford St
Suite 201 Somerville, MA 02143
+1 617 855 0762
sds@formlabs.com

Supplier:

Germany

Formlabs GmbH
Nalepastr. 18
Berlin, . 12459
+49 30 700 146 501

1.4 Emergency telephone number:

European Union

CHEMTREC (EMEA)

+44 20 3885 0382 (24/7)

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008 (CLP):

Skin sensitization, category 1

Chronic aquatic hazard, category 2

Hazard-determining components of labeling:

Urethane Dimethacrylate

Isobornyl Methacrylate

Additional Information: None

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Hazard pictograms:



Signal Word: Warning

Hazard statements:

H317 May cause an allergic skin reaction

H411 Toxic to aquatic life with long lasting effects

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear protective gloves, protective clothing and eye protection.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 2 of 14

Rigid 10K Resin

P273 Avoid release to the environment

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P363 Wash contaminated clothing before reuse

P391 Collect spillage

P501 Dispose of contents and container in accordance with local, regional, national, and international regulations.

2.3 Other hazards: None known

SECTION 3: Composition/information on ingredients

3.1 Substance: Not applicable.

3.2 Mixture:

Identification	EU REACH Registration No.	Name	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Weight %
CAS number: 7631-86-9 EC number: 231-545-4	-	Filler	Not classified	55-75
CAS number: 72869-86-4 EC number: 276-957-5	-	Urethane Dimethacrylate	Skin Sens. 1; H317 Aquatic Chronic 2; H411	15-25
CAS number: 7534-94-3 EC number: 231-403-1	-	Isobornyl Methacrylate	Skin Irrit. 2; H315 STOT SE 3 (RI); H335 Aquatic Chronic 3; H412 Eye Irrit. 2; H319	7-10

Additional information: None

Full Text of H and EUH statements: See section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

Following inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. If respiratory symptoms develop or persist, seek medical advice/attention.

Following skin contact:

Wash affected area with plenty of soap and water. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, seek medical advice/attention.

Following eye contact:

Immediately rinse eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. If eye irritation develops or persists, seek medical advice/attention.

Following ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 3 of 14

Rigid 10K Resin

Self-Protection of the first aider:

Not determined or not available.

4.2 Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment:

Not determined or not available.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

5.2 Special hazards arising from the substance or mixture:

Thermal decomposition may produce irritating/toxic fumes/gases.

5.3 Advice for firefighters

Personal protection equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA).

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

6.2 Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

6.3 Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

6.4 Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 4 of 14

Rigid 10K Resin

7.1 Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

7.2 Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

7.3 Specific end use(s):

Refer to Section 1 (Recommended Use).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Bulgaria	Filler	7631-86-9	TWA: 0.07 mg/m ³ (Free silicon dioxide, amorphous, synthetic from condensation and electrothermal processes - respirable fraction)
	Filler	7631-86-9	TWA: 4 mg/m ³ (Free silicon dioxide, amorphous and crystalline, from natural sedimentation [opal, chalcedony, etc], inhalable fraction)
	Filler	7631-86-9	TWA: 10 mg/m ³ (Free silicon dioxide, amorphous, synthetic from condensation and electrothermal processes, inhalable fraction)
	Filler	7631-86-9	TWA: 1 mg/m ³ (Free silicon dioxide, amorphous and crystalline, from natural sedimentation [opal, chalcedony, etc], respirable fraction)
Croatia	Filler	7631-86-9	8-Hour TWA: 6 mg/m ³ (total dust)
	Filler	7631-86-9	8-Hour TWA: 2.4 mg/m ³ (respirable dust)
Cyprus	Filler	7631-86-9	8-Hour TWA: 5 mg/m ³ (Silicon dioxide [amorphous] [particles > 5 micrometers])
	Filler	7631-86-9	8-Hour TWA: 2 mg/m ³ (Silicon dioxide [amorphous] [particles < 5 micrometers])
Czech Republic	Filler	7631-86-9	8-Hour TWA: 4 mg/m ³ (dust)
Estonia	Filler	7631-86-9	8-Hour TWA: 2 mg/m ³ (fine dust - respirable fraction)
Latvia	Filler	7631-86-9	8-Hour TWA: 1 mg/m ³
Poland	Filler	7631-86-9	8-Hour TWA: 10 mg/m ³ (inhalable fraction)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 5 of 14

Rigid 10K Resin

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Filler	7631-86-9	8-Hour TWA: 2 mg/m ³ (respirable fraction)
Slovakia	Filler	7631-86-9	8-Hour TWA: 0.3 mg/m ³ (Silica, amorphous (fused silica, fused silica, fumes, burnt diatomaceous earth)
Slovenia	Filler	7631-86-9	8-Hour TWA: 4 mg/m ³ (inhalable fraction)
Austria	Filler	7631-86-9	8-Hour TWA: 4 mg/m ³ (inhalable)
Belgium	Filler	7631-86-9	8-Hour TWA: 10 mg/m ³
Finland	Filler	7631-86-9	8-Hour TWA: 5 mg/m ³
Germany (TRGS 900)	Filler	7631-86-9	8-Hour TWA: 4 mg/m ³ (inhalable)
Ireland	Filler	7631-86-9	8-Hour TWA: 6 mg/m ³ (inhalable fraction)
	Filler	7631-86-9	8-Hour TWA: 2.4 mg/m ³ (respirable fraction)
United Kingdom	Filler	7631-86-9	TWA: 6 mg/m ³ (inhalable)
	Filler	7631-86-9	TWA: 2.4 mg/m ³ (respirable)
Germany (MAK)	Filler	7631-86-9	8-Hour TWA: 4 mg/m ³ (inhalable fraction)
	Filler	7631-86-9	8-Hour TWA: 4 mg/m ³ (inhalable)
Denmark	Filler	7631-86-9	8-Hour TWA: 2 mg/m ³ (inhalable)
	Filler	7631-86-9	STEL: 4 mg/m ³ (inhalable)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Derived No Effect Level (DNEL):

Ingredient Name: Urethane Dimethacrylate

CAS #: 72869-86-4

Workers - Systemic Effects	Acute - Oral	Not determined or not applicable.
	Acute - Inhalation	No exposure expected
	Acute - Dermal	No hazard identified
	Chronic - Oral	Not determined or not applicable.
	Chronic - Inhalation	3.3 mg/m ³
	Chronic - Dermal	1.3 mg/kg bw/day
Workers - Local Effects	Acute - Oral	Not determined or not applicable.
	Acute - Inhalation	No exposure expected
	Acute - Dermal	Hazard identified but no DNEL available
	Chronic - Oral	Not determined or not applicable.
	Chronic - Inhalation	No exposure expected
	Chronic - Dermal	Hazard identified but no DNEL available
General Population - Systemic Effects	Acute - Oral	No hazard identified
	Acute - Inhalation	No exposure expected
	Acute - Dermal	No hazard identified
	Chronic - Oral	0.3 mg/kg bw/day
	Chronic - Inhalation	0.6 mg/m ³
	Chronic - Dermal	0.7 mg/kg bw/day

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 6 of 14

Rigid 10K Resin

General Population - Local Effect	Acute - Oral	Not determined or not applicable.
	Acute - Inhalation	No exposure expected
	Acute - Dermal	No exposure expected
	Chronic - Oral	Not determined or not applicable.
	Chronic - Inhalation	No exposure expected
	Chronic - Dermal	Hazard identified but no DNEL available

Ingredient Name: Filler

CAS #: 7631-86-9

Workers - Systemic Effects	Acute - Oral	Not determined or not applicable.
	Acute - Inhalation	Hazard identified but no DNEL available
	Acute - Dermal	Hazard identified but no DNEL available
	Chronic - Oral	Not determined or not applicable.
	Chronic - Inhalation	Hazard identified but no DNEL available
	Chronic - Dermal	Hazard identified but no DNEL available
Workers - Local Effects	Acute - Oral	Not determined or not applicable.
	Acute - Inhalation	Hazard identified but no DNEL available
	Acute - Dermal	Hazard identified but no DNEL available
	Chronic - Oral	Not determined or not applicable.
	Chronic - Inhalation	Hazard identified but no DNEL available
	Chronic - Dermal	Hazard identified but no DNEL available
General Population - Systemic Effects	Acute - Oral	Hazard identified but no DNEL available
	Acute - Inhalation	Hazard identified but no DNEL available
	Acute - Dermal	Hazard identified but no DNEL available
	Chronic - Oral	Hazard identified but no DNEL available
	Chronic - Inhalation	Hazard identified but no DNEL available
	Chronic - Dermal	Hazard identified but no DNEL available
General Population - Local Effect	Acute - Oral	Not determined or not applicable.
	Acute - Inhalation	Hazard identified but no DNEL available
	Acute - Dermal	Hazard identified but no DNEL available
	Chronic - Oral	Not determined or not applicable.
	Chronic - Inhalation	Hazard identified but no DNEL available
	Chronic - Dermal	Hazard identified but no DNEL available

Predicted No Effect Concentration (PNEC):

Ingredient Name: Urethane Dimethacrylate

CAS #: 72869-86-4

Environmental Protection Target	PNEC
Fresh water	0.01 mg/L
Freshwater sediments	4.56 mg/kg sediment dw
Marine water	0.001 mg/L
Marine sediments	0.46 mg/kg sediment dw
Microorganisms in sewage treatment	3.61 mg/L
Soil (agricultural)	0.91 mg/kg soil dw
Air	No hazard identified
Oral (Secondary Poisoning)	No exposure expected

Ingredient Name: Filler

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 7 of 14

Rigid 10K Resin

CAS #: 7631-86-9

Environmental Protection Target	PNEC
Fresh water	No hazard identified
Freshwater sediments	No hazard identified
Marine water	No hazard identified
Marine sediments	No hazard identified
Microorganisms in sewage treatment	No hazard identified
Soil (agricultural)	No hazard identified
Air	No hazard identified
Food chain	No exposure expected

Information on monitoring procedures:

Not determined or not applicable.

8.2 Exposure controls

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Product (substance / mixture) related measures to prevent exposure:	Not determined or not applicable.
Instruction measures to prevent exposure:	Not determined or not applicable.
Organisational measures to prevent exposure:	Not determined or not applicable.
Technical measures to prevent exposure:	Not determined or not applicable.

Risk management measures to control exposure:

Not determined or not applicable.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 8 of 14

Rigid 10K Resin

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	White liquid
Odor	Characteristic acrylate
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>100°C
Flash point (closed cup)	>93.5°C
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not flammable
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	1.63 g/cm ³
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	1896 cps @ 25°C; 933 cps @ 35°C
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

9.2 Other information

None.

SECTION 10: Stability and reactivity

10.1 Reactivity:

Not reactive under recommended handling and storage conditions.

10.2 Chemical stability:

Stable under recommended handling and storage conditions.

10.3 Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.
Stable under recommended handling and storage conditions.

10.4 Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.
Avoid storage >38°C (100°F) and exposure to light/direct sunlight and heat.

10.5 Incompatible materials:

Polymerization initiators, including peroxides, strong oxidizing agents, alcohols, copper, copper alloys, carbon steel, iron, rust, and strong bases.

10.6 Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 9 of 14

Rigid 10K Resin

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Urethane Dimethacrylate	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
Isobornyl Methacrylate	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rabbit: >3000 mg/kg
Filler	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg
	inhalation	LC50 Rat: > 5.01 mg/L (4 h, dust)

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Isobornyl Methacrylate	Causes skin irritation

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Isobornyl Methacrylate	Causes serious eye irritation

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:

No data available.

Substance data:

Name	Result
Urethane Dimethacrylate	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Urethane Dimethacrylate	Not Applicable

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 10 of 14

Rigid 10K Resin

Name	Classification
Filler	Group 3

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Isobornyl Methacrylate	May cause respiratory irritation

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Urethane Dimethacrylate	Fish LC50 Danio rerio: 10.1 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 1.2 mg/L (48 hr)
Isobornyl Methacrylate	Fish LC50 Danio rerio: 1.79 mg/L (96 hours)
	Aquatic Invertebrates EC50 Daphnia magna: 2.57 mg/L (48 hours)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 11 of 14

Rigid 10K Resin

Chronic (long-term) toxicity

Assessment:

Toxic to aquatic life with long lasting effects.

Product data: No data available.

Substance data:

Name	Result
Urethane Dimethacrylate	Aquatic Plants NOEC <i>Desmodesmus subspicatus</i> : 0.21 mg/L (72 hr)
Isobornyl Methacrylate	Aquatic Invertebrates NOEC <i>Daphnia magna</i> : 0.233 mg/L (21 days)

12.2 Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Urethane Dimethacrylate	The substance is not readily biodegradable (22% degradation in 28 days).
Isobornyl Methacrylate	Readily biodegradable

12.3 Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Filler	BCF: 3.16 L/kg

12.4 Mobility in soil

Product data: No data available.

Substance data:

Name	Result
Urethane Dimethacrylate	The substance has moderate potential to adsorb to organic soil and sediment particles (log K _{oc} : 3.66 dimensionless).
Filler	Mobile (log K _{oc} : 1.337)

12.5 Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment:

Urethane Dimethacrylate	This substance is not PBT.
Isobornyl Methacrylate	This substance is not PBT.
Filler	This substance is not PBT.

vPvB assessment:

Urethane Dimethacrylate	This substance is not vPvB.
Isobornyl Methacrylate	This substance is not vPvB.
Filler	This substance is not vPvB.

12.6 Other adverse effects: No data available.

12.7 Hazard to the ozone layer

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 12 of 14

Rigid 10K Resin

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Product / Packaging disposal:

Dispose contaminated packages in a safe manner in accordance with local and national regulations. Do not allow the product to be released into the environment.

Waste codes / waste designations according to LoW: Not determined or not available.

13.1.2 Waste treatment-relevant information: Not determined or not available.


13.1.3 Sewage disposal-relevant information: Not determined or not available.

13.1.4 Other disposal recommendations:


Do not discharge into public wastewater or surface waters. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

SECTION 14: Transport information

International Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of < 5L provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

International Carriage of Dangerous Goods by Inland Waterways (ADN)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of < 5L provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

International Maritime Dangerous Goods (IMDG)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate


Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)


Initial preparation date: 10.26.2022

Page 13 of 14

Rigid 10K Resin

UN transport hazard class(es)	9	
Packing group	III	
Environmental hazards	Marine Pollutant	
Special precautions for user	None	
Additional Information	This product is not regulated as a dangerous good when transported in sizes of < 5L provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN3082	
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate	
UN transport hazard class(es)	9	
Packing group	III	
Environmental hazards	Marine Pollutant	
Special precautions for user	None	
Additional Information	This product is not regulated as a dangerous good when transported in sizes of ≤ 5L provided the packaging meets the general provisions of 5.0.2.4.1, 5.0.2.6.1 and 5.0.2.8.	

Transport in bulk according to Annex II of MARPOL and the IBC Code	
Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

European regulations

Inventory listing (EINECS): All ingredients are listed or exempt.

REACH SVHC candidate list: None of the ingredients are listed.

REACH SVHC Authorizations: None of the ingredients are listed.

REACH Restriction: None of the ingredients are listed.

Water hazard class (WGK) (Product): Not determined.

Water hazard class (WGK) (Substance):

Ingredient Name	CAS	Class
Urethane Dimethacrylate	72869-86-4	Water hazard class 1: slightly hazardous to water
Isobornyl Methacrylate	7534-94-3	Water hazard class 1: slightly hazardous to water
Filler	7631-86-9	Non-hazardous to water

Other regulations

Germany TA Luft:

Ingredient Name	CAS	Class	Base Emission Rate	Max Concentration
Filler	7631-86-9			

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and (EC) No. 1907/2006 (REACH)

Initial preparation date: 10.26.2022

Page 14 of 14

Rigid 10K Resin

Additional information: Not determined.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Abbreviations and Acronyms: None

Classification procedure:

Classification according to Regulation (EC) No. 1272/2008 (CLP)	Method Used
Skin sensitization, category 1	Calculation method
Chronic aquatic hazard, category 2	Calculation method

Summary of classification(s) in section 3:

Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 2	Chronic aquatic hazard, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3 (RI)	Specific target organ toxicity - single exposure, category 3, respiratory tract irritation
Aquatic Chronic 3	Chronic aquatic hazard, category 3
Eye Irrit. 2	Eye Irritation, category 2

Summary of hazard statements in section 3:

H317	May cause an allergic skin reaction
H411	Toxic to aquatic life with long lasting effects
H315	Causes skin irritation
H335	May cause respiratory irritation
H412	Harmful to aquatic life with long lasting effects
H319	Causes serious eye irritation

Disclaimer:

This product has been classified in accordance with EC No. 1272/2008 (CLP), as amended by Commission Regulation (EU) 2019/521 and Commission Delegated Regulation (EU) 2020/217, and EC No. 1907/2006 (REACH). The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation, and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 10.26.2022

Revision Notes:

Revision Date	Notes
2022-10-26	Revision 1.02

End of Safety Data Sheet